





## SPRAY PAINT HEAT RESISTANT 400C



THEORETICAL  
COVERAGE



HEAT RESIS-  
TANT



RUST STOP

Air-drying Heat resistant spray is an easy-to-use aerosol paint with a heat-resistance of up to +400°C. Examples of use: external surfaces of fire places, boilers, chimneys and grills and vehicle exhausts where the surface temperature does not exceed +400 °C. Do not forget to cover nearby surfaces during painting! Apply new layer within 15min. After application let the surface dry at +20 °C for 15 minutes.

**BINDER:** Silicon

**HEAT RESISTANCE:** 400°C

**STORAGE STABILITY:** 60 months

**SIZE:** 400ml


**SALES QTY:**

400ml: 6 pcs

### USAGE INSTRUCTIONS:

When using the product indoors, ensure that the area within at least a 5-meter radius of the painted object is protected. Paint dust is lightweight and can spread over long distances through ventilation.

### MATERIAL



METAL



IN AND OUT


### HARDNESS



3 MIN  
SHAKE




25 CM  
SPRAY DISTANCE



SPRAY PATTERN



5-10 MIN  
TIME BETWEEN LAY-  
ERS



3 LAYERS  
LAYERS



CLEAN UP



30 MIN  
TOUCH DRY



24H  
FINAL DRYING



SILICONE RESIN  
SOLVENT BASED

## MASTON Spray paint Heat resistant 400C

Art. No.	MASTON Spray paint Heat resistant 400C	Color	Barcode
400121	Spraypaint Heat resistant +400°C black 400ml		6412494001212