





## SPRAYPAINT HEAT RESISTANT 600°C



THEORETICAL COVERAGE




HEAT RESISTANT



IN AND OUT

This MASTON HEAT RESISTANT SPRAY IS easy-to-use aerosol paint with a HEAT-RESISTANCE of up to + 600 °C and it is suited for the external surfaces of furnaces, boilers, chimneys, grills, vehicle dampers and similar objects, the operation temperature of which does not exceed + 600 °C. After application let the surface dry at + 20 °C for 30 minutes. To harden, heat to + 200 °C 60 min. When several layers of paint are used the surface should be also heated in between applications.

### MATERIAL



METAL



IN AND OUT

**BINDER:** Silicon

**DEGREE OF GLOSS (DIN 67530 60 °):**  
matt 0-25 gloss units

**HEAT RESISTANCE:** 600°C

**STORAGE STABILITY:** 60 months

**SIZE:** 400ml

**SALES QTY:**  
400ml: 6 pcs

### USAGE INSTRUCTIONS:

When using the product indoors, ensure that the area within at least a 5-meter radius of the painted object is protected. Paint dust is lightweight and can spread over long distances through ventilation.

### RECOAT:

always, 5 minutes in between layers  
heat 60min in 200 degrees to harden


### HARDNESS



SHAKE UPSIDE DOWN




SPRAY DISTANCE




SPRAY PATTERN



TIME BETWEEN LAYERS



LAYERS



CLEAN UP



TOUCH DRY







FINAL HEAT HARDENED



SOLVENT BASED

## MASTON Spraypaint Heat resistant 600°C

Art. No.	MASTON Spraypaint Heat resistant 600°C	Color	Barcode
400996	Spraypaint Heat resistant +600°C silver 400ml		6412494009966
710221	Spraypaint Heat resistant +600°C black 400ml		6412497102213
710221-EU	Spraypaint Heat resistant 600°C Black 400ml		6412490034368
400996-EU	Spraypaint Heat resistant 600°C Silver 400ml		6412490034245
710222-EU	Spraypaint Heat resistant 600°C White 400ml		6412490035365