






WOOD STOVE & BBQ PAINT



THEORETICAL COVERAGE



HEAT RESISTANT




VERY HARD SURFACE



NO RUN DOWN SURFACE

Easy-to-use SPRAY PAINT FOR WOOD STOVES, BBQ'S, fire places, stoves, chimneys etc. Heat resistant up-to +450°C. Clean the surface of soot and other impurities. Sand with sandpaper 400 if necessary. Best painting temperature +20 °C. Remember to protect the areas outside the object. After painting let the paint dry at least for one hour. Heat the object and take care of necessary ventilation when heated the first time. Grey contains small amount of metallic pigmentation to give the color genuine stove outlook.

MATERIAL



METAL



IN AND OUT

BINDER: Silicon

DEGREE OF GLOSS (DIN 67530 60 °):
matt 0-25 gloss units

HEAT RESISTANCE: 450°C

STORAGE STABILITY: 60 months

SIZE: 400ml

SALES QTY:
400ml: 6 pcs

RECOAT:
always, 5 minutes in between

HARDNESS



SAFETY GEAR




3 MINUTES
SHAKE UPSIDE DOWN




25CM
SPRAY PATTERN



5 MIN
TIME BETWEEN LAYERS



3 LAYERS
LAYERS



CLEAN UP



30 MIN
TOUCH DRY



24H
FINAL DRYING



SILICONE RESIN
SOLVENT BASED

MASTON Wood Stove & BBQ Paint

| Art. No. | MASTON Wood Stove & BBQ Paint | Color | Barcode |
|------------|---|-------|---------------|
| 1801004 | Spraypaint Wood Stove & BBQ Black 450°C 400ml | ● | 6412490017828 |
| 1801004-EU | Spraypaint Wood Stove & BBQ Black 450°C 400ml | ● | 6412490036058 |