





SPRAYPAINT RAL 9005



THEORETICAL COVERAGE



WIDE SPRAY NOZZLE

Maston RAL paint corresponds to the RAL paint standard favoured by professionals and the industry. High-quality quick-drying alkyd paint. Suited for wooden, stone, metal, glass and most plastic surfaces. Suitable for both indoor and outdoor applications.

BINDER: Alkyd

DEGREE OF GLOSS (DIN 67530 60 °):
satin 35-50 gloss units

HEAT RESISTANCE: 80°C

STORAGE STABILITY: 60 months

SIZE: 400ml

SALES QTY:
400ml: 6 pcs

USAGE INSTRUCTIONS:

When using the product indoors, ensure that the area within at least a 5-meter radius of the painted object is protected. Paint dust is lightweight and can spread over long distances through ventilation.


RECOAT:

RECOAT IN 5-15 minutes
OR AFTER 7 days
Otherwise film disturbance might occur
Final hardness after 7 days

MATERIAL



WOOD



BRICK



PLASTIC




GLASS



CARDBOARD



WICKER



METAL



NOT STYRO-FOAM



IN AND OUT


HARDNESS



3 MIN SHAKE




15CM SPRAY DISTANCE



SPRAY PATTERN



30MIN - 7 DAYS TIME BETWEEN LAYERS



4 LAYERS 2-4



CLEAN UP



30 MIN TOUCH DRY



FINAL HARDNESS 24H



FINAL DRYING 7 DAYS

MASTON Spraypaint RAL 9005

Art. No.	MASTON Spraypaint RAL 9005	Color	Barcode
400400	Spraypaint RAL 9005 Black satin 400ml		6412494004008