

www.maston.fi





FROSTED GLASS EFFECT SPRAY









WIDE SPRAY COVERAGE NOZZLE

NO RUN DOWN

HARDNESS SOFT



CLEAN

CLEAN UP





SPRAY DISTANCE



TIME BETWEEN LAY-



2 LAYERS **LAYERS**

SOLVENT BASED ACRYL

SOLVENT BASED

SPRAY PATTERN

Frosted Glass Effect acrylic spray paint for glass and most hard plastic surfaces. Ideal for use in small decorative items such as lanterns and vases and also for larger glass surfaces eg. glass surfaces, windows, glass doors, sliding doors, shower walls and windows of saunas.

Test the suitability on plastic surfaces by spaying a small test batch on an invisible spot. Some plastics, such as polycarbonates or acrylics might react with the solvents of the product. Paint at least two layers and let dry in between of the layers until matt.

Gloss: below 20 (matt).

Coverage: around 2-3m2 depending on the layer thickness.

Drying times (20 °C): Dust dry 5 - 10 min, touch dry 15 min., dry 24 hours. Drying time depends on the temperature, the humidity and the layer thickness.

Heat resistance: +110 ° C.

BINDER: Acryl

DEGREE OF GLOSS (DIN 67530 60°):

matt 0-25 gloss units

STORAGE STABILITY: 60 months

SIZE: 400ml

SALES QTY:

400ml: 6 pcs

When using the product indoors, ensure that the area within at least a 5-meter radius of the painted object is protected. Paint dust is lightweight and can spread over long distances through ventilation.





MASTON Frosted Glass Effect Spray

| Art. No. | MASTON Frosted Glass Effect Spray | Color | Barcode |
|----------|---------------------------------------|---------|---------------|
| 1801008 | Spraypaint Frosted glass effect 400ml | \circ | 6412490032555 |

