



RADIATOR SPRAY PAINT



THEORETICAL COVERAGE



WIDE SPRAY NOZZLE



QUICK DRYING



NO RUN DOWN SURFACE

MASTON RADIATOR SPRAY PAINT is high quality, fast-drying acrylic paint especially made for radiators. Very good coverage. Thanks to its fast drying characteristics, surface becomes touch-dry in 10 – 20 minutes. Temperature resistance 120 °C.

BINDER: Acryl

DEGREE OF GLOSS (DIN 67530 60 °):

satin 35-50 gloss units
gloss 80-100 gloss units

HEAT RESISTANCE: 120°C


STORAGE STABILITY: 60 months

SIZE: 400ml

SALES QTY:
400ml: 6 pcs

RECOAT:
always, 5 minutes in between layers

MATERIAL



METAL



IN


HARDNESS



3 MIN SHAKE




15 CM SPRAY DISTANCE




SPRAY PATTERN



5 MIN TIME BETWEEN LAYERS



2 LAYERS



CLEAN UP



15 MIN TOUCH DRY



24H FINAL DRYING



SOLVENT BASED ACRYL SOLVENT BASED

MASTON Radiator Spray Paint

Art. No.	MASTON Radiator Spray Paint	Color	Barcode
1801003	Spraypaint Radiator paint 400ml	○	6412490017811
1801032-EU	Spraypaint Radiator Magnolia Gloss 400ml	○	6412490035327
1801033-EU	Spraypaint Radiator Silver Satin 400ml	●	6412490035334
1801003-EU	Spraypaint Radiator White Gloss 400ml	○	6412490034122
1801003S-EU	Spraypaint Radiator White Satin 400ml	○	6412490035310