







## **WOOD STOVE & BBQ PAINT**









SURFACE

Easy-to-use SPRAY PAINT FOR WOOD STOVES, BBQ'S, fire places, stoves, chimneys etc. Heat resistant up-to +450°C. Clean the surface of soot and other impurities. Sand with sandpaper 400 if necessary. Best painting temperature +20 °C. Remember to protect the areas outside the object. After painting let the paint dry at least for one hour. Heat the object and take care of necessary ventilation when heated the first time. Grey contains small amount of metallic pigmentation to give the color genuine stove outlook.

MATERIAL





METAL



IN AND OUT







SHAKE UPSIDE DOWN



SPRAY PATTERN





**LAYERS CLEAN UP** 





SILICONE RESIN SOLVENT BASED

**BINDER:** Silicon

#### DEGREE OF GLOSS (DIN 67530 60°):

matt 0-25 gloss units

**HEAT RESISTANCE:** 450°C

**STORAGE STABILITY:** 60 months

SIZE: 400ml

### **SALES QTY:**

400ml: 6 pcs

#### **USAGE INSTRUCTIONS:**

When using the product indoors, ensure that the area within at least a 5-meter radius of the painted object is protected. Paint dust is lightweight and can spread over long distances through ventilation.

#### RECOAT:

always, 5 minutes in between





# **MASTON Wood Stove & BBQ Paint**

Art. No.	MASTON Wood Stove & BBQ Paint	Color	Barcode
1801004	Spraypaint Wood Stove & BBQ Black 450°C 400ml		6412490017828
1801004-EU	Spraypaint Wood Stove & BBQ Black 450°C 400ml		6412490036058

