




GALVA PRO SPRAY



THEORETICAL COVERAGE



NO CORROSION



NO RUN DOWN SURFACE




SAFETY GEAR




3 MIN SHAKE



20-25CM SPRAY DISTANCE



LAYERS 2-4



10MIN TIME BETWEEN LAYERS



20MIN TOUCH DRY



24H FINAL DRYING



7DAYS FINAL HARDNESS



USE ONLY SAME SERIES



ALKYD SOLVENT BASED

Maston Galva Pro spray paint is a 2-in-1 product that can be used as a standalone coating or as both a primer and a topcoat. Overpainting: Only with itself (using Galva Pro series products). The paint is suitable for almost all metals (e.g., iron, aluminum, stainless steel, acid-resistant steel, and galvanized steel), as well as wooden surfaces. It offers excellent rust protection and has been tested according to the ASTM B117-2019 standard, with a tested durability of 400 hours. Suitable for Both Indoor and Outdoor Use

Key Features:

- Easy and quick to use
- Provides excellent and long-lasting corrosion protection, resulting in longer reapplication intervals
- Smooth and even surface
- Free from toluene, lead, and chromates
- 2-in-1 – primer and topcoat combined

Technical Information:

- Binder: Solvent-based alkyd
- Gloss level: Matte
- Heat resistance: +80°C
- Storage: Store in a cool, dry place at +5 – +40°C
- Shelf life: Unopened package, 36 months from manufacturing date

Instructions for use:

- Shake the can for approximately 3 minutes before painting.
- Spray from a distance of about 20–25 cm.
- Apply the first coat as a thin mist layer, then follow with slightly thicker layers.

Repainting:

- Repainting: Only with Galva Pro series products, with an evaporation time of 10 minutes between coats.
- For optimal adhesion, ensure the surface is sanded or blast-cleaned (thoroughly cleaned and roughened), free of contaminants, and completely dry before painting.

When using the product indoors, ensure the surrounding area is protected within at least a 5-meter radius in all directions. Fine paint dust is lightweight and can spread over long distances through ventilation

DEGREE OF GLOSS (DIN 67530 60 °):

matte 0-25 gloss units






STORAGE STABILITY: 36 months

SIZE: 500ml

SALES QTY:

500ml: 6 pcs

MASTON Galva Pro spray

Art. No.	MASTON Galva Pro spray	Color	Barcode
4001806	Maston Galva pro spray Red 500ml		6412490047009
4001803	Maston Galva pro spray Silver 500ml		6412490046996
4001801	Maston Galva pro spray Black 500ml		6412490046972
4001810	Maston Galva pro spray Dark Grey 500ml		6412490047016
4001802	Maston Galva pro spray White 500ml		6412490046989