

www.maston.fi



ZINC SPRAY

THEORETICAL COVERAGE		ТОР	ZINC SPRAYS are q for protecting weld Suitable for any me and welded areas o paints. Available in for electric galvaniz ATTENTION!High vi
MATERIAL			minute after the sh the can upside dov
			ZINC DRY CONTEN
			400171 Zinc dry co
METAL IN AND OUT	-		400172 Zinc dry co
HARDNESS 2	3	4 5	BINDER: Zink
SOFT		HARD	DEGREE OF GLOS
CLEAN	2MIN	25 CM	matt 0-25 gloss uni HEAT RESISTANCI STORAGE STABILI
CLEAN WITH BRUSH	SHAKE	SPRAY DISTANCE	
15 MIN BETWEEN LAYERS LAYERS	CLEAN UP	20 MIN TOUCH DRY	SIZE: 400ml SALES QTY: 400ml: 6 pcs
	ERPAINT ONLY ACRY OVERPAINT		USAGE INSTRUCT When using the pro of the painted obje distances through RECOAT: always

quick-drying, durable anti-corrosive agents for any metal, particularly ded seams, drilled holes and other areas from metal corrosion. netal repair, for instance fixing damaged zinc surfaces, covering drilled or any anticorrosive applications. Not to be overpainted with alkyd two versions; dark grey zinc for cold galvanized metals and alu-zinc ized metals.

viscosity. To avoid valve blocking the can must be shaked at least one haking balls inside the can become audible. Clean after use by turning own and spray until only propellant comes out.

NT AND SALT SPRAY TEST RESULTS:

ontent > 92 %, 1000h salt spray

ontent > 90 %, 320h salt spray

SS (DIN 67530 60 °): nits

:E: 200°C

.ITY: 60 months

TIONS:

roduct indoors, ensure that the area within at least a 5-meter radius ect is protected. Paint dust is lightweight and can spread over long ventilation.





MASTON • WWW.MASTON.FI • MASTON@MASTON.FI



MASTON Zinc Spray

Art. No.	MASTON Zinc Spray	Color	Barcode
400172-EU	Spray Aluminium Zinc 400ml	\bigcirc	6412490034238
400171	Spray Zinc 400ml		6412494001717
400172	Spray Aluminium Zinc 400ml	\bigcirc	6412494001724
400171-EU	Spray Zinc 400ml		6412490036027

