




ZINC SPRAY



THEORETICAL COVERAGE
1,5M²



HEAT RESISTANT
0°C



RUST STOP

MATERIAL



METAL



IN AND OUT

HARDNESS



CLEAN

CLEAN WITH BRUSH




2MIN

SHAKE



25 CM

SPRAY DISTANCE



15 MIN BETWEEN LAYERS
LAYERS



CLEAN UP



20 MIN
TOUCH DRY



1H
FINAL DRYING



ONLY ACRYL
OVERPAINT



SOLVENT BASED ZINC
SOLVENT BASED

ZINC SPRAYS are quick-drying, durable anti-corrosive agents for any metal, particularly for protecting welded seams, drilled holes and other areas from metal corrosion. Suitable for any metal repair, for instance fixing damaged zinc surfaces, covering drilled and welded areas or any anticorrosive applications. Not to be overpainted with alkyd paints. Available in two versions; dark grey zinc for cold galvanized metals and alu-zinc for electric galvanized metals.

ATTENTION! High viscosity. To avoid valve blocking the can must be shaken at least one minute after the shaking balls inside the can become audible. Clean after use by turning the can upside down and spray until only propellant comes out.

ZINC DRY CONTENT AND SALT SPRAY TEST RESULTS:

400171 Zinc dry content > 92 %, 1000h salt spray

400172 Zinc dry content > 90 %, 320h salt spray

BINDER: Zink

DEGREE OF GLOSS (DIN 67530 60 °):

matt 0-25 gloss units

HEAT RESISTANCE: 200°C

STORAGE STABILITY: 60 months

SIZE: 400ml

SALES QTY:

400ml: 6 pcs

USAGE INSTRUCTIONS:

When using the product indoors, ensure that the area within at least a 5-meter radius of the painted object is protected. Paint dust is lightweight and can spread over long distances through ventilation.

RECOAT:

always

MASTON Zinc Spray

Art. No.	MASTON Zinc Spray	Color	Barcode
400172-EU	Spray Aluminium Zinc 400ml		6412490034238
400171	Spray Zinc 400ml		6412494001717
400172	Spray Aluminium Zinc 400ml		6412494001724
400171-EU	Spray Zinc 400ml		6412490036027