





ACRYLIC LACQUER



THEORETICAL COVERAGE



WIDE SPRAY NOZZLE



QUICK DRYING



NO RUN DOWN SURFACE

GLOSSY LACQUER ACRYL provides a non-fading, weatherproof protective layer to various acrylic or alkyd paint covered surfaces. Thanks to its great adhesion the Lacquer Acryl could be applied directly to zinc-coated and aluminium surfaces without any separate priming. The lacquer provides treated surfaces with an efficient protection against oxidation. In between applying the coats of lacquer allow a few minutes for drying. Dust-dry in 15 minutes, touch-dry in 2 hours, and completely dry in 4 hours. Please note that varnishing alkyd based surfaces must be performed wet-on-wet.

HARDNESS



BINDER: Acryl

DEGREE OF GLOSS (DIN 67530 60 °):
gloss 80-100 gloss units

HEAT RESISTANCE: 120°C

STORAGE STABILITY: 60 months

SIZE: 400ml

SALES QTY:
400ml: 6 pcs



CLEAN




SHAKE



**15 CM
SPRAY DISTANCE**



**5 MIN
TIME BETWEEN LAYERS**



**2 LAYERS
LAYERS**



CLEAN UP



**15
TOUCH DRY**



**FINAL HARDNESS
24H**



**ACRYL
SOLVENT BASED**

MASTON Acrylic Lacquer

Art. No.	MASTON Acrylic Lacquer	Color	Barcode
400332	Spray Lacquer ACRYL 400ml	○	6412494003322