





## ACRYLIC LACQUER



**THEORETICAL COVERAGE**



**WIDE SPRAY NOZZLE**



**QUICK DRYING**



**NO RUN DOWN SURFACE**

GLOSSY LACQUER ACRYL provides a non-fading, weatherproof protective layer to various acrylic or alkyd paint covered surfaces. Thanks to its great adhesion the Lacquer Acryl could be applied directly to zinc-coated and aluminium surfaces without any separate priming. The lacquer provides treated surfaces with an efficient protection against oxidation. In between applying the coats of lacquer allow a few minutes for drying. Dust-dry in 15 minutes, touch-dry in 2 hours, and completely dry in 4 hours. Please note that varnishing alkyd based surfaces must be performed wet-on-wet.

**HARDNESS**



**BINDER:** Acryl

**DEGREE OF GLOSS (DIN 67530 60 °):**

gloss 80-100 gloss units

**HEAT RESISTANCE:** 120°C

**STORAGE STABILITY:** 60 months

**SIZE:** 400ml

**SALES QTY:**

400ml: 6 pcs

**USAGE INSTRUCTIONS:**

When using the product indoors, ensure that the area within at least a 5-meter radius of the painted object is protected. Paint dust is lightweight and can spread over long distances through ventilation.



**CLEAN**




**SHAKE**




**15 CM  
SPRAY DISTANCE**



**5 MIN  
TIME BETWEEN LAYERS**



**2 LAYERS  
LAYERS**



**CLEAN UP**



**15  
TOUCH DRY**



**FINAL HARDNESS  
24H**



**ACRYL  
SOLVENT BASED**

## MASTON Acrylic Lacquer

| Art. No. | MASTON Acrylic Lacquer    | Color                                                                               | Barcode       |
|----------|---------------------------|-------------------------------------------------------------------------------------|---------------|
| 400332   | Spray Lacquer ACRYL 400ml |  | 6412494003322 |