




## POLYSTYRENE PRIMER



**THEORETICAL COVERAGE**



**HIGH FILLIG POWER**




**FLEXIBLE**



**OVERPAINTABLE SPRAY**

MASTON POLYSTYRENE PRIMER provides perfect protection for all polystyrene base materials. It forms a protective coating on the surface and eliminates penetration of solvents. It also smoothens the rough surface by filling the uneven structure of polystyrene. Let the surface dry around 2 hours and overpaint with any acrylic or water-based paint. ATTENTION! Alkyd based paints might cause reaction of the surface.

### MATERIAL



**STYROFOAM**



**IN AND OUT**

**BINDER:** Waterbased

**DEGREE OF GLOSS (DIN 67530 60 °):**

matt 0-25

**HEAT RESISTANCE:** 80°C

**STORAGE STABILITY:** 36 months

**SIZE:** 400ml

**SALES QTY:**

400ml: 6 pcs

**RECOAT:**

always, 5 minutes in between layers or topcoat after 2h


### HARDNESS




**CLEAN UP CLEAN**




**3 MIN SHAKE**



**15 CM SPRAY DISTANCE**



**SPRAY PATTERN**



**CLEAN UP**



**5 MIN TIME BETWEEN LAYERS**



**2 H TOUCH DRY**




**OVERPAINT AFTER 2H OVERPAINT**



**WATER BASED ALKYD WATER BASED**

## MASTON Polystyrene Primer

Art. No.	MASTON Polystyrene Primer	Color	Barcode
400523-EU	Spray Polystyrene Primer 400ml		6412490035617
400523	Spray Polystyrene Primer 400ml		6412490039196