




POLYSTYRENE PRIMER



THEORETICAL COVERAGE



HIGH FILLIG POWER



FLEXIBLE



OVERPAINTABLE SPRAY

MASTON POLYSTYRENE PRIMER provides perfect protection for all polystyrene base materials. It forms a protective coating on the surface and eliminates penetration of solvents. It also smoothens the rough surface by filling the uneven structure of polystyrene. Let the surface dry around 2 hours and overpaint with any acrylic or water-based paint. ATTENTION! Alkyd based paints might cause reaction of the surface.

MATERIAL



STYROFOAM



IN AND OUT

BINDER: Waterbased

DEGREE OF GLOSS (DIN 67530 60 °):

matt 0-25

HEAT RESISTANCE: 80°C

STORAGE STABILITY: 60 months

SIZE: 400ml

SALES QTY:

400ml: 6 pcs

USAGE INSTRUCTIONS:

When using the product indoors, ensure that the area within at least a 5-meter radius of the painted object is protected. Paint dust is lightweight and can spread over long distances through ventilation.

RECOAT:

always, 5 minutes in between layers or topcoat after 2h

HARDNESS



CLEAN



3 MIN SHAKE



15 CM SPRAY DISTANCE



SPRAY PATTERN



CLEAN UP



5 MIN TIME BETWEEN LAYERS



2 H TOUCH DRY



OVERPAINT AFTER 2H OVERPAINT



WATER BASED ALKYD WATER BASED

MASTON Polystyrene Primer

Art. No.	MASTON Polystyrene Primer	Color	Barcode
400523-EU	Spray Polystyrene Primer 400ml		6412490035617
400523	Spray Polystyrene Primer 400ml		6412490039196