





## HEAT RESISTANT PAINT 400°C



**THEORETICAL COVERAGE**



**HEAT RESISTANT**



**IN AND OUT**

MASTON HEAT RESISTANT air-drying paint with a heat resistance of +400 °C is also suited for dampers, bike cylinders, furnace doors, boilers, outdoor grills, chimneys, the operation temperature of which does not exceed +400 °C.

For optimum results: Clean and dry the surface to be treated. Stir the paint carefully before use. Use a brush or a spray for application. If necessary, apply the second layer directly on the wet surface or only after 24 hours of drying at room temperature.

For paint dilution and tool cleaning: Maston Xylen.

**BINDER:** Silicon

**DEGREE OF GLOSS (DIN 67530 60 °):**  
matt 0-25 gloss units

**HEAT RESISTANCE:** 400°C

**STORAGE STABILITY:** 60 months

**SIZE:** 10l, 1l, 250ml

**SALES QTY:**

10l: 1 pcs  
1l: 2 pcs  
250ml: 5 pcs

**USAGE INSTRUCTIONS:**

When using the product indoors, ensure that the area within at least a 5-meter radius of the painted object is protected. Paint dust is lightweight and can spread over long distances through ventilation.

**RECOAT:**

in 15 minutes or after 24 hours

**MATERIAL**



**METAL**



**IN AND OUT**

**HARDNESS**




**CLEAN WITH BRUSH**



**STIR**



**TIME BETWEEN LAYERS**



**2 LAYERS IF NECESSARY LAYERS**



**30 MIN TOUCH DRY**



**24H FINAL DRYING**



**CLEAN WITH XYLENE**



**SILICONE RESIN SOLVENT BASED**

## MASTON Heat Resistant Paint 400°C

Art. No.	MASTON Heat Resistant Paint 400°C	Color	Barcode
604811	Paint Heat resistant black +400 °C 10l	●	6412490032524

## MASTON Heat Resistant Paint 400°C

Art. No.	MASTON Heat Resistant Paint 400°C	Color	Barcode
604801	Paint Heat resistant black +400 °C 1l	●	6412490004668

## MASTON Heat Resistant Paint 400°C

Art. No.	MASTON Heat Resistant Paint 400°C	Color	Barcode
604800	Paint Heat resistant black +400 °C 250ml	●	6412496048000