

www.maston.fi





RUBBERCOMP RUBBER COATING









FLEXIBLE

RUBBERcomp® Synthetic Rubber Coating. RUBBERcomp® is a multi-purpose, air drying specialty rubber coating. It can be easily applied by dipping, brushing, or spraying. It protects coated items against moisture, acids, abrasion, corrosion, and skidding/ slipping, and provides a comfortable, controlled grip.

RUBBERcomp remains flexible and stretchy over time, and will not crack or become brittle in extreme weather conditions. We recommend applying at least 4 layers.

It has been tested and proven in temperatures from -30°C to 90°C.

MATERIAL





BRICK







RUBBER TO 1K STOP

BINDER: Rubber

SIZE: 1

SALES QTY: 11: 2 pcs















NOT STYRO-IN AND OUT

DEGREE OF GLOSS (DIN 67530 60°):

matt 0-25 gloss units satin 35-50 gloss units gloss 80-100 gloss units

HEAT RESISTANCE: 90°C

STORAGE STABILITY: 60 months





CARDBOARD WICKER



















SOLVENT BASED RUBBER SOLVENT BASED

FINAL HARDNESS





MASTON Rubbercomp rubber coating

Art. No.	MASTON Rubbercomp rubber coating	Color	Barcode
1911215	RUBBERcomp Black semi gloss 1L		6412490027599
1912220	RUBBERcomp White 1L	0	6412490027605

