





ZINC COLD GALVANIZED, BRUSHABLE



THEORETICAL COVERAGE



HEAT RESISTANT



RUST STOP

ZINC BRUSHABLE is quick-drying and durable anti-corrosive agent for any metal, particularly for protecting welding seams, drilling holes and other areas for metal corrosion. Suitable for any metal repair, for instance fixing damaged zinc surfaces, covering drilling and welding points or any anti-corrosive applications. Not to be overpainted with alkyd paints. Available in two versions; dark grey zinc for cold galvanized metals and alu-zinc for electric galvanized metals.

Mix the paint properly before use! A zinc coating can be applied using a brush, roller or electrical paint gun. Thinning and tool cleaner: Maston xylene. Drying times (+23 °C): dust-dry in ca 15 min, touch dry 30 min. Overpainting: after 1 hour.

BINDER: Zink

DEGREE OF GLOSS (DIN 67530 60 °):
matt 0-25 gloss units

HEAT RESISTANCE: 200°C

STORAGE STABILITY: 60 months

SIZE: 1l , 250ml

SALES QTY:
1l: 2 pcs
250ml: 5 pcs

RECOAT:
always

MATERIAL



METAL



IN AND OUT

HARDNESS



CLEAN

CLEAN WITH BRUSH




STIR

STIR



30 MIN

TOUCH DRY



1-2 LAYERS LAYERS



AFTER 1-2H OVERPAINT



NO ALKYD TO ZINC



CLEAN

CLEAN WITH XYLENE



ZINC

SOLVENT BASED

MASTON Zinc Cold Galvanized, brushable

Art. No.	MASTON Zinc Cold Galvanized, brushable	Color	Barcode
5410171	Zinc Cold Galvanized 1l, brushable	○	6412490004736

MASTON Zinc Cold Galvanized, brushable

Art. No.	MASTON Zinc Cold Galvanized, brushable	Color	Barcode
5410170	Zinc Cold Galvanized 250 ml, brushable	○	6412490040215