






## SPRAY COPPER GREASE



EASY TO SPRAY



TECHNICAL 2 IN 1 NOZZLE



REMOVE SEAL

Copper Grease spray has excellent adhesion and anticorrosion properties and is heat resistant from -40 °C to +1100 °C. Protects against seizure caused by corrosion, heat and chemical attack. Examples of use: exhaust pipe connections, wheel bolts and nuts, clutches, screw threads, spark plugs, battery terminals, brakes, in welding to avoid splashes etc. Before applying please check that the surface is dry and free from grease and loose particles. Resistant against water, salts, acids and resins. Instructions: Shake well. Apply direct to parts that require protection.

Attention! Is not suitable for ABS and ASR brake systems.


**HEAT RESISTANCE:** 1100°C

**STORAGE STABILITY:** 36 months

**SIZE:** 400ml

**SALES QTY:**  
400ml: 6 pcs

**MATERIAL**



METAL



IN AND OUT




CLEAN

CLEAN WITH CLOTH



SHAKE



SPRAY DISTANCE



SAFETY

SAFETY GLOVES



SOLVENT BASED

## MASTON Spray Copper Grease

| Art. No. | MASTON Spray Copper Grease | Color | Barcode       |
|----------|----------------------------|-------|---------------|
| 400606   | Spray Copper Grease 400ml  |       | 6412490026929 |