



SPRAY HOLLOW SECTION 500ML



RUST STOP



FLEXIBLE



HIGH FILLING
POWER



SOUND ABSORB-
ING

MASTON HOLLOW SECTION is a waxy protection agent for your car's door and skirting panels. Also suitable as a protector during storage of machines and metal parts. Penetrates into the smallest gaps, removing moisture and protecting against rust.

How to do it: Cover all surfaces that do not require treatment. Shake the container for approx. 3 minutes before use. Spray several thin layers, letting the paste dry in between sprayings. This will give an even and protective result. Shake the container during the process to keep the paste liquid and spreadable.

HARDNESS



STORAGE STABILITY: 60 months

SIZE: 500ml

SALES QTY:


500ml: 6 pcs, 0 pcs




CLEAN WITH CLOTH
AND SOLVENT



3 MIN
SHAKE




SPRAY DISTANCE



4 LAYERS
LAYERS



5-15 MIN
TIME BETWEEN LAY-
ERS



CLEAN UP






2-3H
FINAL DRYING



WAX
SOLVENT BASED

MASTON Spray Hollow section 500ml

Art. No.	MASTON Spray Hollow section 500ml	Color	Barcode
4150300-L	Spray HOC-30 500ml with long hose		6412490027193
4150300-EU	Spray Hollow section Auto 500ml		6412490036126
4150300	Spray Hollow section HOC-30 Auto 500ml		6412490000158