




STONECHIP COATING 1L (SCREW-TOP JAR)



THEORETICAL COVERAGE



RUST STOP



FLEXIBLE



HIGH FILLING POWER

HARDNESS




CLEAN

CLEAN WITH BRUSH



3 MIN

SHAKE



4 LAYERS

1-4

LAYERS



15 MIN

TIME BETWEEN LAYERS



45 MIN

TOUCH DRY



2H

FINAL DRYING



CLEAN

CLEAN WITH CLOTH AND SOLVENT



RUBBER

SOLVENT BASED

Maston stonechip coating is protection agent for your car's door and skirting panels. Also suitable as a protector during storage of machines and metal parts. Penetrates into the smallest gaps, removing moisture and protecting against rust.

Instructions: Cover all surfaces that do not require treatment. Shake the container for approx. 3 minutes before use. Use bar 4-5. Spray several thin layers, letting the paste dry in between sprayings. This will give an even and protective result. About 15 minutes in between the layers. Shake the container during the process to keep the paste liquid and spreadable. Coverage 1,5m2.

Drying time at +20 °C: Dry to touch after 45 minutes, completely dry after 2 hours..

Topcoat: make sure that the mass is completely dry and stuck the surface. For stain removal we recommend Maston Thinner.

STORAGE STABILITY: 60 months

SIZE: 1l

SALES QTY:

1l: 12 pcs

MASTON Stonechip coating 1L (screw-top jar)

Art. No.	MASTON Stonechip coating 1L (screw-top jar)	Color	Barcode
4150512	Stonechip coating STH-51 grey Auto 1L (screw-top jar)		6412490000202
4150511	Stonechip coating STH-51 black Auto 1L (screw-top jar)		6412490000196