




## STONECHIP COATING 1L (SCREW-TOP JAR)



**THEORETICAL COVERAGE**



**RUST STOP**



**FLEXIBLE**



**HIGH FILLING POWER**


**HARDNESS**



**CLEAN WITH BRUSH**



**3 MIN SHAKE**



**1-4 LAYERS**



**15 MIN TIME BETWEEN LAYERS**



**45 MIN TOUCH DRY**



**2H FINAL DRYING**



**CLEAN WITH CLOTH AND SOLVENT**



**RUBBER SOLVENT BASED**

Maston stonechip coating is protection agent for your car's door and skirting panels. Also suitable as a protector during storage of machines and metal parts. Penetrates into the smallest gaps, removing moisture and protecting against rust.

Instructions: Cover all surfaces that do not require treatment. Shake the container for approx. 3 minutes before use. Use bar 4-5. Spray several thin layers, letting the paste dry in between sprayings. This will give an even and protective result. About 15 minutes in between the layers. Shake the container during the process to keep the paste liquid and spreadable. Coverage 1,5m<sup>2</sup>.



Drying time at +20 °C: Dry to touch after 45 minutes, completely dry after 2 hours.. Topcoat: make sure that the mass is completely dry and stuck the surface. For stain removal we recommend Maston Thinner.

**STORAGE STABILITY:** 60 months

**SIZE:** 1l

**SALES QTY:**  
1l: 12 pcs

## MASTON Stonechip coating 1L (screw-top jar)

Art. No.	MASTON Stonechip coating 1L (screw-top jar)	Color	Barcode
4150512	Stonechip coating STH-51 grey Auto 1L (screw-top jar)		6412490000202
4150511	Stonechip coating STH-51 black Auto 1L (screw-top jar)		6412490000196