




## UNDERBODY COATING UBC-11 AUTO 1L (SCREW-TOP JAR)



**THEORETICAL  
COVERAGE**



**RUST STOP**



**FLEXIBLE**



**HIGH FILLIG  
POWER**




**CLEAN WITH BRUSH**



**3 MIN  
SHAKE**



**UBC BAR SEAL GUN**



**1-2  
LAYERS**




**30 MIN  
TIME BETWEEN LAY-  
ERS**



**12H  
TOUCH DRY**



**24H  
FINAL DRYING**



**CLEAN  
CLEAN WITH CLOTH**



**BITUMEN  
SOLVENT BASED**

Maston Underbody Coating is a bitumen-based coating designed for long-term gravel protection of front and rear spoilers, sills, side skirts, wheel arches, and other underbody parts. It is flexible, durable, and provides excellent protection against rust and gravel.

This coating also has sound-dampening properties, reducing noise inside the vehicle. It is resistant to salt, moisture, acids, alkaline substances, and other corrosive environments. The product can be applied drip-free and adheres well to a wide range of materials, especially car underbodies. It is also compatible with original PVC undercoatings.

Important: This product can only be overcoated with bitumen-based products (it is not paintable). Do not apply to the exhaust, brake system, or engine parts. For high corrosion protection, bare metal should first be treated with an anti-corrosion primer before applying this underbody coating.

Instructions for Use:

1. Surface Preparation: Ensure the surface is clean, dry, and free of grease. Cover all areas that do not require treatment.
2. Application:
  - Stir well before use.
  - Use a working pressure of 4-5 bar.
  - Spray from a distance of approximately 30 cm.
  - Apply several thin layers, allowing each layer to dry for about 30 minutes for an even and protective finish.
  - Shake the container occasionally during application to maintain a liquid and spreadable consistency.

Application temperature: 10 – 25 ° C


3. Coverage: 1,4 m<sup>2</sup> per container.
4. Drying Time (at +20°C):
  - Touch dry: 12-16 hours
  - Fully cured: 24 hours
5. Stain Removal: We recommend using Maston Thinner or Xylene.

**STORAGE STABILITY:** 60 months

**SIZE:** 1l

**SALES QTY:**  
1l: 12 pcs

## MASTON Underbody coating UBC-11 Auto 1L (screw-top jar)

Art. No.	MASTON Underbody coating UBC-11 Auto 1L (screw-top jar)	Color	Barcode
4150110	Underbody coating UBC-11 Auto 1L (screw-top jar)		6412490000134