



SPRAY UNDERBODY COATING AUTO 500ML


RUST STOP

FLEXIBLE

**HIGH FILLIG
POWER**

**SOUND ABSORB-
ING**

HARDNESS



Maston Underbody coating is a quick-drying bitumen-based protector for your car's chassis. It is flexible, hard-wearing, and provides excellent protection against rust. Instructions: Clean the surface carefully. Cover all surfaces that do not require treatment. Shake the container for approx. 3 minutes before use. Spray from a distance of approx. 30 cm. Spray several thin layers, letting the paste dry in between sprayings. This will give an even and protective result. Shake the container during the process to keep the paste liquid and spreadable. Clean nozzle after use: turn container upside down and press the nozzle until only propellant comes out. Drying time Approx 2 h at +20 °C. For stain removal we recommend Maston Thinner.


STORAGE STABILITY: 60 months

SIZE: 500ml

SALES QTY:
500ml: 6 pcs


CLEAN WITH BRUSH

**3 MIN
SHAKE**

**20-100 CM
SPRAY DISTANCE**

**4 LAYERS
3-4
LAYERS**

CLEAN UP



**15 MIN
TIME BETWEEN LAY-
ERS**

**2H
FINAL DRYING**

**CLEAN WITH CLOTH
AND SOLVENT**

**BITUMEN
SOLVENT BASED**

MASTON Spray Underbody coating Auto 500ml

Art. No.	MASTON Spray Underbody coating Auto 500ml	Color	Barcode
4150100	Spray Underbody coating Auto 500ml		6412490000127
4150100-EU	Spray Underbody coating Auto 500ml		6412490034252