




SPRAY FILLER



THEORETICAL
COVERAGE



HIGH FILLING
POWER



RUST STOP



STRONG BOND

MASTON SPRAY FILLER compounds of car refinish filler, acrylic binder and additives. It has good filling power, it levels fast and dries quickly. Easy to sand, but can also be painted with overcoat directly, no sanding needed. Due to the acrylic base Maston fillers and primers are compatible with most of the overcoats, also with synthetic or nitro based primers. Suitable for metal, aluminium and wood.

New layer can be applied wet-on-wet or wet-on dry. Easy to sand, for sanding after drying we recommend wet-sandpapers grain, final grain 400-600.

HARDNESS



DEGREE OF GLOSS (DIN 67530 60 °):

matt 0-25 gloss units

STORAGE STABILITY: 60 months

SIZE: 400ml

SALES QTY:

400ml: 1 pcs

RECOAT:


always, 5 minutes in between layers



3 MIN
SHAKE



15 CM
SPRAY DISTANCE




SPRAY PATTERN



5 MIN
TIME BETWEEN LAYERS



SEVERAL LAYERS
LAYERS



CLEAN UP



30 MIN
TOUCH DRY



FINAL HARDNESS
24H



ACRYL
SOLVENT BASED

MASTON Spray filler

Art. No.	MASTON Spray filler	Color	Barcode
4780100	Spray sprayfiller 400ml		6412490002503