




## FIBERGLASS PUTTY 600G



SAFETY GEAR



Maston Fiberglass Putty is a fiberglass-reinforced plastic filler designed for repairing holes and cracks in fiberglass structures. It is suitable for fiberglass (GFK/GRP), polyester fillers, acrylic and epoxy primers, provided the surfaces are in good condition. It can also be applied over well-sanded 2K primers. Additionally, it is suitable for repairing metal surfaces and can be used on bare or zinc-coated steel and aluminum after proper smoothing and degreasing.

NOTE: Do not apply the filler directly onto 1K primers.

Key Features:

- Excellent adhesion to metal
- Superior mechanical strength and flexibility
- Short curing time
- Good sanding properties

Instructions for Use:

1. Sand the surface thoroughly.
2. Clean the surface of grease and dirt.
3. Mix 2% hardener thoroughly into the filler.
4. Mix only as much as you can use within 4–7 minutes
5. Apply a layer (maximum 5 mm) and allow it to dry. If needed, apply additional layers, ensuring each layer is fully dry before the next application.
6. After curing, perform dry sanding:
  - Coarse sanding: P80–P120 sandpaper
  - Finishing sanding: P120–P320 sandpaper
7. Store the filler in a tightly sealed container, in a cool place, protected from sunlight.

Additional Information:

- Drying time: 20–30 min at +20°C (Lower temperatures will considerably extend the drying time.)
- IR drying process is not recommended.
- Surface Treatment After Filling: 2K polyester fillers and putty
- Excessive hardener may affect the final paint color shade.

Safety Precautions:

When working with 2K products, it is recommended to use protective equipment:

- Wear safety goggles, gloves, and a respirator.
- Ensure good ventilation in the working area.
- Clean tools immediately after use.
- Always follow the manufacturer's safety instructions.

## Storage and Packaging:

- Color: Green
- Gloss level: Matte
- Sales unit: 18 pcs
- Storage conditions: Store at 15–25°C in a sealed container, in a dry and cool place, away from heat sources and direct sunlight.
- Shelf life:
- Filler: 12 months from the manufacturing date
- Hardener: 18 months from the manufacturing date

**STORAGE STABILITY:** 12 months**SIZE:** 600ml**SALES QTY:**

600ml: 18 pcs

## MASTON Fiberglass putty 600g

Art. No.	MASTON Fiberglass putty 600g	Color	Barcode
706206	Fiberglass putty 600g		6412490047092