



## PLASTIC PUTTY



**HIGH FILLIG POWER**



**STRONG BOND**



**QUICK DRYING**



**SANDABLE**

Maston Plastic putty for smoothing surfaces before painting applications. Fills and evens out cracks and dents in fibreglass structures, metal sheet surfaces and concrete walls. Stir well before use! \*Instructions:\* 1. Sand the surface carefully. 2. Clean off grease and dirt. 3. Mix 1 % of hardener to the putty. 4. Choose the amount of mixture so that you can use it during the next 5 minutes. After that the mixture starts to harden. 5. After hardening, prepare the surface with sanding machine. 6. Store the kit tightly closed in a cool place and protect it from sunlight.

**HARDNESS**



**DEGREE OF GLOSS (DIN 67530 60 °):**

matt 0-25 gloss units


**STORAGE STABILITY:** 6 months

**SIZE:** 500ml

**SALES QTY:**  
500ml: 12 pcs



**SANDABLE**



**CLEAN WITH CLOTH**



**5 MIN TOUCH DRY**



**1% PERCENT HARDENER**



**POLYESTER SOLVENT BASED**

## MASTON Plastic putty

Art. No.	MASTON Plastic putty	Color	Barcode
706105	Plastic putty Auto 0,5kg		6412497061053