




## SPRAY FILLER



**THEORETICAL COVERAGE**



**HIGH FILLING POWER**



**RUST STOP**



**STRONG BOND**

MASTON SPRAY FILLER compounds of car refinish filler, acrylic binder and additives. It has good filling power, it levels fast and dries quickly. Easy to sand, but can also be painted with overcoat directly, no sanding needed. Due to the acrylic base Maston fillers and primers are compatible with most of the overcoats, also with synthetic or nitro based primers. Suitable for metal, aluminium and wood.

New layer can be applied wet-on-wet or wet-on dry. Easy to sand, for sanding after drying we recommend wet-sandpapers grain, final grain 400-600.

### HARDNESS



### DEGREE OF GLOSS (DIN 67530 60 °):

matt 0-25 gloss units

**STORAGE STABILITY:** 60 months

**SIZE:** 400ml

**SALES QTY:**

400ml: 1 pcs

### RECOAT:


always, 5 minutes in between layers



**3 MIN SHAKE**



**15 CM SPRAY DISTANCE**




**SPRAY PATTERN**



**5 MIN TIME BETWEEN LAYERS**



**SEVERAL LAYERS LAYERS**



**CLEAN UP**



**30 MIN TOUCH DRY**



**24H FINAL HARDNESS**



**ACRYL SOLVENT BASED**

## MASTON Spray filler

Art. No.	MASTON Spray filler	Color	Barcode
4780100	Spray sprayfiller 400ml		6412490002503