




## UNIVERSAL PUTTY / PLASTIC PUTTY 450G


**SAFETY GEAR**

**2 PARTS HARDENER 100 PARTS PUTTY**  
**MIXING RATIO**

**STIR**  
**STIR**

**4-7MIN**  
**USE IN**

**1 LAYER**  
**MAX 3MM**  
**LAYERS**

**MAX 60°C 5-7MIN**  
**INFRARED TOUCH DRY**

**20-30MIN**  
**TOUCH DRY**

Maston Universal Putty is a plastic filler designed for repairing deep and medium-depth dents and holes. Its excellent filling and leveling properties, combined with a fast drying time, ensure easy application. It is suitable for various surfaces, including sanded fiberglass, wood (after smoothing and degreasing), galvanized steel, aluminum, and bare steel. It can also be applied over polyester filler or primer, provided the surface is in good condition.

Key Features:

- Easy to apply
- Excellent adhesion
- Good sanding properties
- Fast drying

Multiple thin layers can be applied; however, each layer must fully harden before applying the next. Do not exceed a 3 mm thickness. The working time is 4–6 minutes at 20°C.

Safety Precautions:

When working with 2K products, it is recommended to use protective equipment:

- Wear safety goggles, gloves, and a respirator.
- Ensure good ventilation in the working area.
- Clean tools immediately after use.
- Always follow the manufacturer's safety instructions.

Additional Information:

- Color: Yellowish
- Gloss level: Matte
- Sales unit: 18 pcs
- Storage: Store at 15–25°C in a sealed container, in a dry and cool place, away from heat sources and direct sunlight.
- Shelf life:
- Filler: 12 months from the manufacturing date
- Hardener: 18 months from the manufacturing date

**STORAGE STABILITY:** 18 months

**SIZE:** 450ml

**SALES QTY:**  
450ml: 18 pcs

## MASTON Universal putty / Plastic putty 450g

Art. No.	MASTON Universal putty / Plastic putty 450g	Color	Barcode
706104	Universal putty / Plastic putty 450g		6412490047108