MASTON

www.maston.fi



MASTON METAL FILLER 250G


2 PARTS HARDENER +
100 PARTS PUTTY



STIR



TOUCH DRY



SAND DRY

Maston Metal Filler is a 2-component polyester filler containing aluminum pigments. It is especially suitable for car body repairs but can also be used for a variety of other applications.
Ideal for large surfaces, particularly metal substrates exposed to vibration and continuous temperature fluctuations.'
Features
• Excellent adhesion to metal
• High conductivity
• Smooth sanding properties

Application
• On bare steel and aluminum after surface leveling and degreasing
• On galvanized steel after leveling and degreasing
• On sanded fiberglass (GFK/GRP), over polyester filler, acrylic, and epoxy primers – provided the surfaces are in good condition
• On dry and clean concrete and wood surfaces

Optimal working temperature: 15–20 °C (min. 12 °C)
The mixed product remains usable for approximately 4–7 minutes.
Apply in multiple thin layers however, do not exceed 3 mm per application.
Drying time:
Approximately 20–30 minutes at 20 °C.
Lower temperatures will significantly increase drying time.
IR drying time:
5–7 minutes depending on layer thickness.
Do not heat above 60 °C.
Use IR equipment as recommended by the manufacturer.
Wait approximately 5 minutes before starting the IR drying process.

Sanding:
• Coarse dry sanding: grit P80–P120
• Finishing dry sanding: grit P120–P320
Overcoating:
Compatible with most types of fillers and paints.
Color: Grey

Note:
Excessive hardener may cause color deviations in the topcoat.
When working with 2-component products, always use personal protective equipment: safety goggles and a respirator.
Work only in well-ventilated areas.
Clean tools immediately after use.

Storage:
Keep sealed in a dry place at 15–25 °C, protected from direct sunlight, flame, and heat sources.

Shelf life:
• Filler: 12 months from manufacturing date
• Hardener: 18 months from manufacturing date

SIZE: 250ml

SALES QTY:
250ml: 12 pcs

MASTON Maston Metal filler 250g

Art. No.	MASTON Maston Metal filler 250g	Color	Barcode
706106	Maston Metal filler 250g		6412490047375