



SPRAY AUTOACRYL CLEAR COAT



THEORETICAL COVERAGE



QUICK DRYING



VERY HARD SURFACE



UV-PROOF

Maston AutoACRYL lacquer is high quality acrylic clear coat for metal parts, hard plastic parts and rims. Excellent coverage, quick drying time, smooth surface and durable gloss. Instructions: Polish the surface. Prime metal surfaces with primer and plastic surfaces with plastic primer if necessary. The surface has to be clean, dry and free of any grease, wax or silicone.

HARDNESS



BINDER: Acryl

DEGREE OF GLOSS (DIN 67530 60 °):

gloss 80-100 gloss units

HEAT RESISTANCE: 120°C

STORAGE STABILITY: 60 months

SIZE: 500ml

SALES QTY:

500ml: 6 pcs

USAGE INSTRUCTIONS:

Shake can for at least 2-3 minutes also occasionally during painting. Paint a test patch on invisible area first. Start spraying outside the object. Spray at distance of about 25 cm from surface and move the spray slowly on the object. Spray a thin layer first to improve adhesion. Let dry between layers for 3-5 minutes. Thereafter apply 2-3 thin cross layers on the surface and let dry. Repeat if necessary. Drying time: Touch-dry 10-20min. Totally dry 24 hours. Clean the nozzle by turning the can upside down and spray until only propellant comes out.


When using the product indoors, ensure that the area within at least a 5-meter radius of the painted object is protected. Paint dust is lightweight and can spread over long distances through ventilation.



SHAKE




25CM SPRAY DISTANCE




SPRAY PATTERN



CLEAN UP



5MIN TIME BETWEEN LAYERS



LAYERS



15MIN TOUCH DRY



24H FINAL DRYING



SOLVENT BASED ACRYL SOLVENT BASED

MASTON Spray AutoACRYL Clear Coat

Art. No.	MASTON Spray AutoACRYL Clear Coat	Color	Barcode
4303320	Spraypaint AutoACRYL Clear Coat 500ml	○	6412490024970
4303320-EU	Spraypaint AutoACRYL Clear Coat 500ml	○	6412490035952
4303310-EU	Spraypaint AutoACRYL Clear Coat Matt 500ml	○	6412490043773