



## SPRAY AUTOACRYL CLEAR COAT



**THEORETICAL  
COVERAGE**



**QUICK DRYING**



**VERY HARD  
SURFACE**



**UV-PROOF**

Maston AutoACRYL lacquer is high quality acrylic clear coat for metal parts, hard plastic parts and rims. Excellent coverage, quick drying time, smooth surface and durable gloss. Instructions: Polish the surface. Prime metal surfaces with primer and plastic surfaces with plastic primer if necessary. The surface has to be clean, dry and free of any grease, wax or silicone.

**BINDER:** Acryl

**DEGREE OF GLOSS (DIN 67530 60 °):**

gloss 80-100 gloss units

**HEAT RESISTANCE:** 120°C

**STORAGE STABILITY:** 60 months

**SIZE:** 500ml

**SALES QTY:**

500ml: 6 pcs

### USAGE INSTRUCTIONS:

Shake can for at least 2-3 minutes also occasionally during painting. Paint a test patch on invisible area first. Start spraying outside the object. Spray at distance of about 25 cm from surface and move the spray slowly on the object. Spray a thin layer first to improve adhesion. Let dry between layers for 3-5 minutes. Thereafter apply 2-3 thin cross layers on the surface and let dry. Repeat if necessary. Drying time: Touch-dry 10-20min. Totally dry 24 hours. Clean the nozzle by turning the can upside down and spray until only propellant comes out.

When using the product indoors, ensure that the area within at least a 5-meter radius of the painted object is protected. Paint dust is lightweight and can spread over long distances through ventilation.

### HARDNESS




**SHAKE**



**25CM  
SPRAY DISTANCE**




**SPRAY PATTERN**



**CLEAN UP**



**5MIN  
TIME BETWEEN LAY-  
ERS**



**LAYERS**



**15MIN  
TOUCH DRY**



**24H  
FINAL DRYING**



**SOLVENT BASED ACRYL  
SOLVENT BASED**

## MASTON Spray AutoACRYL Clear Coat

Art. No.	MASTON Spray AutoACRYL Clear Coat	Color	Barcode
4303320	Spraypaint AutoACRYL Clear Coat 500ml		6412490024970