



TEAK OIL



THEORETICAL COVERAGE



QUICK DRYING



WEATHER-PROOF



UV-PROOF

Maston Teak Oil is an easy-to-use protecting and caring agent for treating any type of wood. This product cleans and strengthens the timber surface, restoring its natural tone and ensuring resistance to changing climate conditions, and protecting effectively against moisture, dryness, bending, and cleaving.

The product is suitable for both indoor and outdoor applications. We recommend using protective clothing and goggles. Make sure to protect the surrounding surfaces not to be treated by covering these!

MATERIAL



WOOD



IN AND OUT

BINDER: Wood oil

STORAGE STABILITY: 60 months

SIZE: 180ml , 450ml

SALES QTY:

180ml: 6 pcs

450ml: 6 pcs


HARDNESS



USAGE INSTRUCTIONS:

For optimum results: The surface to be treated must be clean and dry, at temperatures + 15 °C and with a moisture content of 80%. Shake before use. Instructions: Apply a thin layer of oil using a cloth (not napped) or brush directly to a clean and dry surface to be treated. Leave to absorb for 15 minutes and remove excess oil using a cloth. In normal circumstances one layer is enough. For new or worn wooden surfaces more layers might be necessary, repeat application if needed. Let the surface dry completely before taking into use. To avoid self-ignition of cloths, soak used clothes and tools in water after use.


Coverage: 8-10 m2/l.



CLEAN WITH CLOTH



USE BRUSH



LAYERS



WIPE OFF AFTER 15 MIN




TOUCH DRY 2H



SOLVENT BASED

MASTON Teak Oil

Art. No.	MASTON Teak Oil	Color	Barcode
605181	Teak Oil 180ml brown		6412490005634
605180	Teak Oil 180ml Transparent		6412496051802

MASTON Teak Oil

Art. No.	MASTON Teak Oil	Color	Barcode
605451	Teak Oil 450ml brown		6412490005641
605450	Teak Oil 450ml Transparent		6412496054506